Impulse Winding Tester

7700/7710/7720

Features

- High voltage calibration
- programmable impulse voltage, low-energy detection without damaging the DUT
- Built-in storage 200 sets testing waveform
- Storage golden sample (DUT) standard waveform in the instrument, and compare with the other sample waveform
- Provides 5 waveform comparison: total area comparison, differential area comparison, wave comparison, futter and corona
- Key lock function to prevent operators from accidentally touching
- Support RS-232, remote and printer interfaces

Applications

Include Inverters, Power Inductors, Transformers, Motors, Wave Filters, Capacitors and Wires









RS-232 🗓 | Remote 🗓 | Printer 🗓

Accessories / Fixtures

Standard

- Power Cord
- HV test red/black cable (7700/7710)
- HV test red cable (7720)
- D-Sub foot switch (F760001)

Optional

- PC Link software (7700/7710)
- RS-232 cable
- Remote control cable

Specifications


| Model Name | 7700 | 7710 | 7720 |
|-----------------------------------|---|-------------|------------|
| Channel | 2 | 2 | 8 |
| Impulse Voltage (programmable) | 200V-5000V | 200V-10000V | 200V-5000V |
| Lowest Inductance | 50μΗ | 100μΗ | 50μΗ |
| Impulse Voltage Accuracy | ±2% | | |
| Measurement Time | 50ms | | |
| Test Items | Total area comparison, differential area comparison, wave comparison, futter and corona | | |

General

| PLC Remote Control | Test, Abort | |
|---|---|--|
| PLC Remote Output Signal | Pass, Fail, HV output, Testing | |
| Built-in Storage | 200 sets testing waveform (7700/7710) 80 sets testing waveform (7720) | |
| Interface | RS-232, Remote, Printer | |
| Power Supply | Voltage 98Vac-132Vac or 192Vac-264Vac | |
| | Frequency 50/60Hz ±5% | |
| Power Consumption | 85VA | |
| Display | 320*240, 5.7" dot-matrix | |
| Environment | Temperature: 10°C-40°C, Humidity: 20-90%RH | |
| Dimension (W*H*D) | 435×145×522mm (7700/7710) 435×190×522mm (7720) | |
| Weight | 8kg (7700/7710), 9kg (7720) | |
| Power Consumption Display Environment Dimension (W*H*D) | Frequency 50/60Hz ±5% 85VA 320*240, 5.7" dot-matrix Temperature: 10°C-40°C, Humidity: 20-90%RH 435×145×522mm (7700/7710) 435×190×522mm (7720) | |

Key feature

Principle of Impulse Winding Test



Detect Layer Short by Compare Damped Oscillation Waveforms

Waveform comparison measurement



Impulse Voltage (programmable) 200V-5000V, storage golden sample (DUT) standard waveform in the instrument, and compare with the other sample waveform.